

# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## MVP Water Slide

Version number: GHS 1.0

Date of compilation: 2015-11-03

### SECTION 1: Identification

#### 1.1 Product identifier

Trade name **MVP Water Slide**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses water sheeting agent

#### 1.3 Details of the supplier of the safety data sheet

MVP Distributing  
2854 S Featherly Way  
Boise, ID 83709  
208-859-6000

Competent person responsible for the SDS  
Robert Blahnik

#### 1.4 Emergency telephone number

Emergency information service **USA 1.800.535.5053, INTL 1.352.323.3500**  
24 hour emergency telephone number.

### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

##### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Annex	-	Hazard class and category	-	Hazard statement code(s)	
B.6		flammable liquids	Cat. 2	(Flam. Liq. 2)	H225
A.1D		acute toxicity (dermal)	Cat. 4	(Acute Tox. 4)	H312
A.2		skin corrosion/irritation	Cat. 2	(Skin Irrit. 2)	H315
A.3		serious eye damage/eye irritation	Cat. 2	(Eye Irrit. 2)	H319
A.8		specific target organ toxicity - single exposure	Cat. 1	(STOT SE 1)	H370
A.8D		specific target organ toxicity - single exposure (narcotic effects, drowsiness)	Cat. 3	(STOT SE 3)	H336

##### Remarks

For full text of H-phrases: see SECTION 16.

##### Hazards not otherwise classified

Very toxic to aquatic life (GHS category 1: aquatic toxicity - acute).  
Repeated exposure may cause skin dryness or cracking.

##### The most important adverse physicochemical, human health and environmental effects

Immediate effects can be expected after short-term exposure. The product is combustible and can be ignited by potential ignition sources.

#### 2.2 Label elements

##### Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

**Signal word** **danger**

##### Pictograms

GHS02, GHS07,  
GHS08



# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## MVP Water Slide

Version number: GHS 1.0

Date of compilation: 2015-11-03

### **Hazard statements**

H225	Highly flammable liquid and vapor.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs.

### **Precautionary statements**

#### **Precautionary statements - prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Wash thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/eye protection/face protection.

#### **Precautionary statements - response**

IF ON SKIN: Wash with plenty of water.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF exposed or concerned: Call a POISON CENTER/doctor.  
Call a POISON CENTER/doctor if you feel unwell.  
Specific treatment (see on this label).  
Take off contaminated clothing and wash it before reuse.  
In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

#### **Precautionary statements - storage**

Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.

#### **Precautionary statements - disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### **Hazardous ingredients for labelling**

ethyl alcohol, acetone

### **2.3 Other hazards**

Repeated exposure may cause skin dryness or cracking.

# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## MVP Water Slide

Version number: GHS 1.0

Date of compilation: 2015-11-03

### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

not relevant (mixture)

#### 3.2 Mixtures

##### Description of the mixture

Name of substance	Identifier	Wt%	Hazard class and category		Hazard statement
ethyl alcohol	CAS No 64-17-5	50 - < 75	B.6 A.1D A.2 A.3 A.8	Flam. Liq. 2 Acute Tox. 4 Skin Irrit. 2 Eye Irrit. 2A STOT SE 1	H225 H312 H315 H319 H370
acetone	CAS No 67-64-1	25 - < 50	B.6 A.3 A.8D	Flam. Liq. 2 Eye Irrit. 2 STOT SE 3	H225 H319 H336
Propan-2-ol	CAS No 67-63-0	5 - < 10	B.6 A.3 A.8D	Flam. Liq. 2 Eye Irrit. 2A STOT SE 3	H225 H319 H336

For full text of abbreviations: see SECTION 16.

### SECTION 4: First-aid measures

#### 4.1 Description of first-aid measures

##### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

##### Following inhalation

In case of respiratory tract irritation, consult a physician. Provide fresh air.

##### Following skin contact

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.

##### Following eye contact

Irrigate copiously with clean, fresh water, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing.

##### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## MVP Water Slide

Version number: GHS 1.0

Date of compilation: 2015-11-03

### SECTION 5: Fire-fighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

water spray, alcohol resistant foam, BC-powder, carbon dioxide (CO<sub>2</sub>)

##### Unsuitable extinguishing media

water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

##### Hazardous combustion products

nitrogen oxides (NO<sub>x</sub>), carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

##### For non-emergency personnel

Remove persons to safety.

##### For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose it.

#### 6.3 Methods and material for containment and cleaning up

##### Advices on how to contain a spill

Covering of drains.

##### Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage (sawdust, kieselgur (diatomite), sand, universal binder).

##### Appropriate containment techniques

Use of adsorbent materials.

##### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal precautions: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## MVP Water Slide

Version number: GHS 1.0

Date of compilation: 2015-11-03

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

##### Recommendations

##### Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools.

##### Warning

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

##### Advice on general occupational hygiene

Wash hands after use. Do not to eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingsuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

##### Managing of associated risks

##### • Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

##### • Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

##### Incompatible substances or mixtures

Observe compatible storage of chemicals.

##### Consideration of other advice

##### Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

##### Packaging compatibilities

Only packagings which are approved (e.g. acc. to DOT) may be used.

#### 7.3 Specific end use(s)

See section 16 for a general overview.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### National limit values

##### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Source
US	acetone	67-64-1	PEL	1,000	2,400			29 CFR OSHA
US	ethyl alcohol (ethanol)	64-17-5	PEL	1,000	1,900			29 CFR OSHA
US	hexone (methyl isobutyl ketone)	108-10-1	PEL	100	410			29 CFR OSHA
US	isopropyl alcohol	67-63-0	PEL	400	980			29 CFR OSHA

# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## MVP Water Slide

Version number: GHS 1.0

Date of compilation: 2015-11-03

### Notation

STEL	Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified.
TWA	Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average.

### Relevant DNELs/DMELs/PNECs and other threshold levels

No data available.

## 8.2 Exposure controls

### Appropriate engineering controls

General ventilation.

### Individual protection measures (personal protective equipment)

#### Eye/face protection

Wear eye/face protection.

#### Skin protection

##### • hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

##### • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state	liquid
Color	colorless
Odor	solvent - like alcohols

#### Other physical and chemical parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	56.5 °C at 101.3 kPa
Flash point	-20 °C at 101.3 kPa (closed cup)
Evaporation rate	not determined
Flammability (solid, gas)	not relevant (fluid)
Explosive limits	
• lower explosion limit (LEL)	2.5 vol%
• upper explosion limit (UEL)	13.5 vol%
Vapor pressure	57.26 hPa at 19.6 °C
Density	0.7943 g/ml
Solubility(ies)	not determined

# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## MVP Water Slide

Version number: GHS 1.0

Date of compilation: 2015-11-03

Partition coefficient n-octanol/water (log KOW)	This information is not available.
Auto-ignition temperature	>363 °C
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s): risk of ignition

• **if heated**

risk of ignition

#### 10.2 Chemical stability

See below "Conditions to avoid".

#### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints to prevent fire or explosion**

Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

**Physical stresses which might result in a hazardous situation and have to be avoided**

strong shocks

#### 10.5 Incompatible materials

There is no additional information.

#### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

**Classification procedure**

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)**

**Acute toxicity**

Harmful in contact with skin.

# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## MVP Water Slide

Version number: GHS 1.0

Date of compilation: 2015-11-03

### Acute toxicity estimate (ATE)

dermal 1,676

### Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	ATE
ethyl alcohol	64-17-5	dermal	1,100

### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

### Summary of evaluation of the CMR properties

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant.

### Carcinogenicity

- National Toxicology Program (United States): none of the ingredients are listed
- IARC Monographs none of the ingredients are listed

Name of substance	Name acc. to inventory	CAS No	wt%	Classification	Remarks	Number
4-methylpentan-2-one	Methyl isobutyl ketone	108-10-1	0.375	2B		Volume 101
ethyl alcohol	Ethanol	64-17-5	65.63	1	in alcoholic beverages	Volume 96, 100E
Propan-2-ol	Isopropyl alcohol	67-63-0	5.25	3		Volume 15, Sup 7, 71

### Legend

- 1 Carcinogenic to humans.  
2B Possibly carcinogenic to humans.  
3 Not classifiable as to carcinogenicity in humans.

### Specific target organ toxicity (STOT)

#### Specific target organ toxicity - single exposure

Causes damage to organs. May cause drowsiness or dizziness.

Hazard category	Target organ	Exposure route
1	several organs	if exposed

#### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## MVP Water Slide

Version number: GHS 1.0

Date of compilation: 2015-11-03

### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

### Other information

Repeated exposure may cause skin dryness or cracking.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity (acute)

Shall not be classified as hazardous to the aquatic environment.

#### Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
ethyl alcohol	64-17-5	LC50	14.2 g/l	fish	96 hours
ethyl alcohol	64-17-5	EC50	12.9 g/l	fish	96 hours
Propan-2-ol	67-63-0	LC50	10,000 mg/l	fish	96 hours

#### Aquatic toxicity (chronic)

#### Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
ethyl alcohol	64-17-5	LC50	>0.08 mg/l	fish	42 d
ethyl alcohol	64-17-5	EC50	22.6 g/l	algae	10 d
ethyl alcohol	64-17-5	ErC50	675 mg/l	algae	4 d
Propan-2-ol	67-63-0	LC50	>10,000 mg/l	aquatic invertebrates	24 h

### 12.2 Persistence and degradability

Data are not available.

#### Degradability of components of the mixture

Name of substance	CAS No	Process	Degradation rate	Time
ethyl alcohol	64-17-5	oxygen depletion	74 %	5 d
Propan-2-ol	67-63-0	oxygen depletion	53 %	5 d

### 12.3 Bioaccumulative potential

Data are not available.

#### Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
ethyl alcohol	64-17-5		-0.35	

### 12.4 Mobility in soil

Data are not available.

# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## MVP Water Slide

Version number: GHS 1.0

Date of compilation: 2015-11-03

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Waste treatment-relevant information

Solvent reclamation/regeneration.

#### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

#### Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

## SECTION 14: Transport information

14.1	UN number	1993
14.2	UN proper shipping name	<b>FLAMMABLE LIQUID, N.O.S.</b>
	<b>Hazardous constituents</b>	ethyl alcohol, acetone
14.3	Transport hazard class(es)	
	Class	3 (flammable liquids)
14.4	Packing group	II (substance presenting medium danger)
14.5	Environmental hazards	none (non-environmentally hazardous acc. to the dangerous goods regulations)
14.6	Special precautions for user	
	There is no additional information.	
14.7	Transport in bulk according to Annex II of MARPOL and the IBC Code	
	The cargo is not intended to be carried in bulk.	

### Information for each of the UN Model Regulations

#### • Transport of dangerous goods by road or rail (49 CFR US DOT)

Index number	1993
Proper shipping name	Flammable liquid, n.o.s.
Class	3
Packing group	II
Danger label(s)	3



Special provisions (SP)	IB2, T7, TP1, TP8, TP28
ERG No	128

# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## MVP Water Slide

Version number: GHS 1.0

Date of compilation: 2015-11-03

### • International Maritime Dangerous Goods Code (IMDG)

UN number 1993  
Proper shipping name FLAMMABLE LIQUID, N.O.S.  
Class 3  
Packing group II  
Danger label(s) 3



Special provisions (SP) 274  
Excepted quantities (EQ) E2  
Limited quantities (LQ) 1 L  
EmS F-E, S-E  
Stowage category E

### • International Civil Aviation Organization (ICAO-IATA/DGR)

UN number 1993  
Proper shipping name Flammable liquid, n.o.s.  
Class 3  
Packing group II  
Danger label(s) 3



Special provisions (SP) A3, 274  
Excepted quantities (EQ) E2  
Limited quantities (LQ) 1 L

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations specific for the product in question

#### National regulations (United States)

#### **SARA TITLE III (Superfund Amendment and Reauthorization Act)**

List of Extremely Hazardous Substances (40 CFR 355) (EPCRA Section 302 and 304) none of the ingredients are listed

Specific Toxic Chemical Listings (40 CFR 372) (EPCRA Section 313) none of the ingredients are listed

Name of substance	CAS No	Remarks	Effective date
Propan-2-ol	67-63-0	Only persons who manufacture by the strong acid process are subject, no supplier notification.	1986-12-31

#### Industry or sector specific available guidance(s)

# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## MVP Water Slide

Version number: GHS 1.0

Date of compilation: 2015-11-03

### NPCA-HMIS® III

Hazardous Materials Identification System (American Coatings Association)

Category	Rating	Description
Chronic	*	Chronic (long-term) health effects may result from repeated overexposure.
Health	2	Temporary or minor injury may occur.
Flammability	3	Materials that can be ignited under almost all ambient temperature conditions.
Physical hazard	0	Materials that are normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosives.
Personal protective equipment	-	

### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States)

Category	Degree of hazard	Description
Flammability	3	Materials that can be ignited under almost all ambient temperature conditions.
Health	2	Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
Instability	0	Materials that are normally stable, even under fire conditions.
Special hazard		

### Right to Know Hazardous Substance List

Name of substance	CAS No	Remarks	Classifications
ethyl alcohol	64-17-5		CA MU TE F3
Propan-2-ol	67-63-0		F3
acetone	67-64-1		F3

#### Legend

CA Carcinogenic.  
F3 Flammable - Third Degree.  
MU Mutagenic.  
TE Teratogenic.

### Proposition 65 List of chemicals

none of the ingredients are listed

Name of substance	CAS No	Remarks	Type of toxicity
ethyl alcohol	64-17-5	in alcoholic beverages	cancer
ethyl alcohol	64-17-5	in alcoholic beverages	developmental

# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## MVP Water Slide

Version number: GHS 1.0

Date of compilation: 2015-11-03

### Relevant European Union (EU) safety, health and environmental provisions

#### Classification according to GHS (1272/2008/EC, CLP)

##### Hazard class

flammable liquids  
serious eye damage/eye irritation  
specific target organ toxicity - single exposure (narcotic effects, drowsiness)

##### Category Hazard class and category

2 (Flam. Liq. 2)  
2 (Eye Irrit. 2)  
3 (STOT SE 3)

## SECTION 16: Other information, including date of preparation or last revision

### 16.2 Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR OSHA	29 CFR §1910.1001 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR § 40 U.S. Department of Transportation
Acute Tox.	acute toxicity
ATE	Acute Toxicity Estimate
BCF	BioConcentration Factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
COD	chemical oxygen demand
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EmS	Emergency Schedule
ERG No	Emergency Response Guidebook - Number
Eye Dam.	seriously damaging to the eye
Eye Irrit.	irritant to the eye
Flam. Liq.	flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IARC Monographs	IARC Monographs on the Evaluation of Carcinogenic Risks to Humans
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
log KOW	n-octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NFPA® 704	National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States)

# Safety Data Sheet

acc. to OSHA, Appendix D to § 1910.1200

## MVP Water Slide

Version number: GHS 1.0

Date of compilation: 2015-11-03

Abbr.	Descriptions of used abbreviations
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	parts per million
Skin Corr.	corrosive to skin
Skin Irrit.	irritant to skin
STOT SE	specific target organ toxicity - single exposure
vPvB	very Persistent and very Bioaccumulative

### 16.3 Key literature references and sources for data

- OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200
- 49 CFR § 172.101 Hazardous Materials Table (DOT)

### 16.4 Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards/Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### 16.5

#### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H225	highly flammable liquid and vapor
H312	harmful in contact with skin
H315	causes skin irritation
H319	causes serious eye irritation
H336	may cause drowsiness or dizziness
H370	causes damage to organs

### 16.7

#### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.